MATERIAL SAFETY DATA SHEET

SECTION I

IDENTITY: E-Z PATCH® # 3 THINSET POOL TILE SETTING CEMENT (DRY SET MORTAR)

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components: Portland Cement (CAS-65997-15-1)
OSHA PEL: 50 Mppcf
ACGIH TLV: 10mg/m3 - TWA
Hazardous Components: Silica Sand (CAS 01-4808-60-7)
OSHA PEL: 0.1mg/m^3 (respirable) 0.3mg/m^3 (total dust)
ACGIH TLV: 0.1mg/m^3 (respirable dust)
Hazardous Components: Clay (12428-46-5)
OSHA PEL: 5mg/m^3 (respirable) 15mg/m^3 (total dust)
ACGIH TLV: 10mg/m^3 - TWA

SECTION III - Physical/Chemical Characteristics

Boiling Point: NA		Specific Gravity:	2.5
Vapor Pressure: NA		Melting Point:	ND
Vapor Density: NA		Evaporation Rate:	NA

Solubility in water: < 1%
Appearance & Odor: White powder – no odor.

SECTION IV - Fire and Explosion Hazard Data

Flash Point: NA Flammable Limits: NA
Extinguishing Media: NA
Special Fire Fighting Procedures: NA
Unusual Fire and Explosion Hazards: NA

SECTION V – Reactivity Data

Stability: Stable
Incompatibility: Mineral Acids
Hazardous Decomposition or byproducts – CO, CO2, Silicon tetra fluoride (with hydrofluoric acid)
Hazardous Polymerization: Will not occur

SECTION VI – Health Hazard Data

Primary Routes of Entry: Inhalation – Yes Skin – Yes Ingestion – No
Health Hazards:
Acute: Portland Cement mortar can dry the skin & cause alkali burns.
Dust can irritate the eyes & upper respiratory system.
Chronic: Dust can cause inflammation of the interior of nose & eyes.
Prolonged exposure to dust over the TLV may cause scarring of lungs & delayed lung injury (silicosis).
Carcinogenicity: NTP-NO IARC Monographs-YES OSHA Regulated-NO
This product itself is not regulated but it contains small amounts of naturally occurring crystalline silica. IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemical to humans (volume 42, 1987) concludes that there is sufficient evidence for the carcinogenicity of crystalline

SECTION VI – Health Hazard Data (con't)

silica to experimental animals, and that there is limited evidence of the carcinogenicity of crystalline silica to humans. IARC Class 2A.

Signs & Symptoms Of Exposure: Shortness of breath, coughing, reddening of eyes.

Medical Conditions Aggravated by Exposure: Hypersensitive individuals may develop allergenic dermatitis.

Emergency and First Aid Procedures: Irrigate eyes with water, wash exposed skin areas with water, remove patient to fresh air. If accidentally ingested mortar may set & cause bowel obstruction-Consult physician.

SECTION VII – Precautions for Safe Handling and Use

Released or Spilled: Collect spills using dustless method, material can be returned to container for later use. Wear OSHA approved respirator for silica dust when cleaning area.

Waste Disposal Method: Mortar can be disposed of as common waste, un-restricted sanitary landfill.

Precautions to be Taken in Handling and Storing: Eliminate exposure to dust, use OSHA approved mask for silica dust, if freshly mixed mortar gets into eyes or contacts skin – flush immediately and repeatedly with water and contact physician immediately.

SECTION VIII – Control Measures

Respiratory Protection: OSHA approved respirator for silica dust.

Ventilation: Local exhaust – YES Mechanical – N/A
Special – N/A Other – N/A

Protective Gloves: Rubber recommended.

Eye Protection: Tight fitting goggles in busy area.

Other Protective Clothing: Barrier cream, boots & clothing should protect skin from dust and wet mortar.

Work/Hygenic Practices: Workers should shower with soap & water after working with mortar.

NA=Not Applicable ND=Not Determined (revised, 01/26/11)

Disclaimer: E-Z Products believes the information contained herein is accurate. However, E-Z Products makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. E-Z Products assumes no responsibility for injury from the use of the product described herein.