

# E-Z PATCH<sup>®</sup> 1

## WHITE POOL PLASTER REPAIR KIT

A EASY TO USE REPAIR KIT THAT LOOKS LIKE ORIGINAL PLASTER

E-Z PRODUCTS

888-439-7282

**NET WT. 50 LB. (22.7 Kg)**

REPAIR KIT CONTAINS 60 fl. OZ. (1.75 liter) LIQUID CEMENT BONDER  
AND APPROX. 50 LB. (22.7 Kg) DRY CEMENT MIX  
COVERAGE: APPROX. 15 SQ. FT. (3/8" DEEP)

### E-Z INSTRUCTIONS:

1. Lower water below repair area. 2. Remove loose cement and chip area down at least 3/8" deep. Clean surface and rinse with water. 3. Add 4 oz, of LIQUID CEMENT BONDER per 3 lb. E-Z PATCH 1 DRY CEMENT MIX. Add water and mix until you get the consistency of "mashed potatoes". Use warm water for faster set and cold water to slow set.

**4a. FOR CRACK REPAIRS** - Crack should be saw-cut & cleaned if not min. 1/8" wide & 1/4" deep. Rub E-Z PATCH 1 deep into crack and remove excess with a moist sponge.

**4b. FOR CHIPS OR LARGER AREAS** -Firmly trowel E-Z PATCH 1 filling the area. Trowel again (not as firmly) flat and smooth. Remove excess from edges with a moist sponge. After patch stiffens, trowel again with a moist trowel flat and smooth for finish.

**You may refill water the next day.**

View our Instructional Repair Video showing how to do this repair at [www.e-zpatch.com](http://www.e-zpatch.com)

**WARNING:** CONTAINS CEMENT, AN ALKALINE SUBSTANCE IRRITATING TO EYES AND SKIN. CONTAINS ACRYLIC RESIN CEMENT BONDER. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

**KEEP OUT OF THE REACH OF CHILDREN**

**MADE IN THE U.S.A.**



6 08695 05010 4