

E-Z PATCH[®] 1 F.S.

WHITE POOL PLASTER REPAIR KIT FOR UNDERWATER OR ABOVE WATER FAST SET REPAIRS

A EASY TO USE REPAIR KIT THAT LOOKS LIKE ORIGINAL PLASTER

E-Z PRODUCTS

888-439-7282

NET WT. 50 LB. (22.7 kg)

**REPAIR KIT CONTAINS 50 LB. (22.25 kg) DRY CEMENT MIX
COVERAGE: APPROX. 15 SQ. FT. (3/8" DEEP)**

E-Z INSTRUCTIONS:

UNDER WATER REPAIRS: 1. Remove loose cement and chip area at least 3/8" deep. 2. Add water sparingly to **E-Z PATCH 1 F.S. DRY CEMENT MIX** and mix it into a very thick consistency enough to be used within 5 min. Use warm water for faster set and cold water to slow set. 3. Wait a couple of minutes (until the materials start to harden), place a little more than needed in your hand covering it inside of your fist or in a plastic bag. Apply at the repair area immediately pressing **E-Z PATCH 1 F.S.** firmly with a rubbing or twisting motion on the area. 4. Slowly flatten smooth and flush with a trowel, clean edges and slowly back away from repair. **Allow repair to set hard before swimming.**

ABOVE WATER REPAIRS: 1. Follow steps 1. & 2. above but do not wait and add a little more water (to adjust setting time longer also add some dry cement from a E-Z PATCH 1 repair kit). **2a. FOR CRACK REPAIRS:** Rub **E-Z PATCH 1 F.S.** deep into crack and remove excess with a moist sponge. **2b. FOR CHIPS OR LARGER AREAS:** Firmly trowel **E-Z PATCH 1 F.S.** filling the area. Trowel flat and smooth. Remove excess from edges with a moist sponge. Trowel once again for a finished repair. ***Allow repair to set hard before filling pool.**

View our instructional repair video showing how to do this repair at www.e-zpatch.com

WARNING: CONTAINS CEMENT, AN ALKALINE SUBSTANCE IRRITATING TO EYES AND SKIN. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

KEEP OUT OF THE REACH OF CHILDREN

MADE IN THE U.S.A.



6 08695 05011 1