

# E-Z PATCH® 24

## ELASTIC CRACK PREVENTER

**Flexible Repair Membrane for  
Pooldeck, Concrete, Coping  
Stone, Plaster or Gunitite  
CRACKS**

**E-Z PRODUCTS  
888-439-7282**

**NET 32 FL. OZ.**

# E-Z PATCH® 24

## **DIRECTIONS:**

**Shake container of E-Z PATCH® #24  
thoroughly (30-60 sec.) before applying.**

**OPTION #1:** Repair cracked area & allow repairs to dry. Apply 2 thin coats of **E-Z Patch® 24** over the repaired cracks using a paint brush & allow to dry 30 min. before applying Paint, Pooldeck or Plaster. (Also seals latex caulking to prevent "bleed through").

**OPTION #2:** Apply 2 coats of **E-Z Patch® 24** to the inside surface of the cracked/ chipped area using a small paint brush prior to doing repairs. Allow to dry 30 min. before applying repair material.

**E-Z PATCH® 24** has a light tan color. Clean-up with XYLENE

**DANGER!** EXTREMELY FLAMMABLE. Do not use near heat, sparks, or open flame. Vapors will accumulate easily and may ignite explosively. Do not smoke. Do not expose to heat or store at temperatures above 120° F. Dispose of according to government regulations. Do not breath vapors. May affect the brain or nervous system causing headaches, dizziness or nausea. Causes nose and throat irritation. If you experience eye watering, headaches or dizziness, wear respiratory protection or leave the area. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. In case of skin contact, wash thoroughly with soap and water. If swallowed, call a doctor immediately. **CONTAINS XYLENE.** NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**KEEP OUT OF THE REACH OF CHILDREN**

**View our Instructional Videos at:  
[www.e-zpatch.com](http://www.e-zpatch.com)**