

**E-Z PATCH®**

**28**

**FLEXIBLE  
VINYL  
LINER  
REPAIR  
SEALANT**

**No patch  
usually  
needed!!**

**Underwater or  
Above Water**

Caution:  
Carefully read cautions  
on back panel

**CLEAR**

NET 4.8 U.S. FL. OZ.

**Bonds to:**  
Vinyl, PVC, Masonry,  
Fiberglass, Metal & Wood

**E-Z DIRECTIONS**  
**FOR VINYL LINER REPAIRS:**

- Surface must be clean.
- Extrude E-Z PATCH 28 onto rip, cut or hole area on vinyl liner.
- Using your wet fingers, even out E-Z PATCH 28 leaving 1/8" thickness and "featheredge" the edges flush with surface.
- If repairing underwater and leak is excessive, use E-Z PATCH 28 to adhere a vinyl patch.

**\*\*E-Z PATCH 28 is also good for sealing cracks, threads and gaskets.**

**CAUTION:** FLAMMABLE, DO NOT USE NEAR IGNITION SOURCES. DO NOT STORE NEAR HEAT OR FLAME. CONTAINS CYCLOHEXANONE, MEK, TOLUENE & V.M.&P. NAPHTHA. USE IN AREAS WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. IF INGESTED, DO NOT INDUCE VOMITING AND CALL A PHYSICIAN IMMEDIATELY. IN CASE OF CONTACT WITH EYES, IMMEDIATELY FLUSH WITH WATER FOR 15 MIN. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. UNCURED PRODUCT MAY IRRITATE THE SKIN. TO CLEAN FROM SKIN, USE MINERAL SPIRITS AND THEN WASH SKIN WITH SOAP AND WATER.

**-KEEP OUT OF THE REACH OF CHILDREN-**

**E-Z PRODUCTS**

**888-439-7282**

**[www.ezpatch.com](http://www.ezpatch.com)**



**\*\*Please do all typeset and bar code on both pages of typeset in Reflex Blue C color on White colored tube background**