

E-Z PATCH[®] 4 F.S.

WHITE POOL TILE GROUT FOR ABOVE WATER OR UNDERWATER FAST SET REPAIRS

AN EASY-TO-USE REPAIR KIT THAT LOOKS LIKE ORIGINAL GROUT

E-Z PRODUCTS
888-439-7282

NET WT. 50 LB. (22.7 Kg)

REPAIR KIT CONTAINS: 50 LB. (22.7 Kg) DRY CEMENT MIX
COVERAGE: APPROX. 150 SQ. FT.

E-Z INSTRUCTIONS:

1. Remove all loose material or grout.
2. Add water to **E-Z PATCH 4 F.S.** DRY CEMENT MIX, (Enough to be used within 5 - 10 min.) and mix (stir) until you get the consistency of "mashed potatoes".
3. Completely fill area to be grouted.
4. Using a sponge, lightly wipe off excess grout leaving joint full and flush.
5. If used above water, also remove any excess residue "haze" off tile with a cloth when dry.
Allow one (1) hour set before swimming.

(E-Z PATCH 4 F.S. can also be used to set tile underwater).

View our instructional repair video showing how to do this repair at www.e-zpatch.com

WARNING: CONTAINS CEMENT, AND ALKALINE SUBSTANCE IRRITATING TO EYES AND SKIN. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

KEEP OUT OF THE REACH OF CHILDREN

MADE IN THE U.S.A.

