



# Clear Acrylic Non-Skid Coating

## For all Cement Surfaces, Flagstone or Brick

**PREMIUM GRADE WATER BASED SEALER THAT SEALS AND PROTECTS  
SURFACES AGAINST SALT WATER, STAINING & SPALLING FROM FREEZING**

### E-Z INSTRUCTIONS:

Detergent scrub or Muratic Acid etch surface and rinse off thoroughly with water or power-wash. Surface must be dry before applying. Surface temperature must be between 60° F and 90°F. Thoroughly mix contents and stir again each time before dipping the paint roller into product to keep the non-skid material in suspension. Apply one coat for re-coating and apply two coats if a new application. Use a 3/8" paint roller cover. Apply thin coats and do not allow coating to puddle. Allow 2 to 4 hours drying time between coats. Coverage is approx. 300 sq. ft. per coat per gallon.

**WARNING:** Contains Acrylic Resin and Polymers. In case of eye contact, flush thoroughly with water. Do not rub eyes. If swallowed, induce vomiting. Consult a Physician immediately. In case of skin contact, flush area immediately with water. Avoid breathing vapors, mists and dusts. If needed use approved respirator. Use only with adequate ventilation. Goggles are recommended while handling this product.

**KEEP OUT OF THE REACH OF CHILDREN**

**MADE IN THE U.S.A.**

**5 US GALLONS**

**E-Z PRODUCTS**

888-439-7282

[www.e-zpatch.com](http://www.e-zpatch.com)