



Liquid Acrylic Bonder & Admixture

For Pooldeck and Concrete Resurfacing

E-Z INSTRUCTIONS:

As a Cement Resurfacing Bonder on Total or Large Area Resurfacing:

Sand off any mineral deposits. Detergent scrub any places where oils are and rinse off with water. Acid wash entire substrate surface and powerwash clean. Surface may be slightly damp or dry when applying.

Apply a coat of full strength (do not add water) Liquid Acrylic Bonder/Admixture to the substrate using a 3/8" or 1/2" paint roller (coverage approx. 2000 sq. ft.) prior to installing a cement resurfacing product **or** Mix Liquid Acrylic Bonder with E-Z Patch #2 Pooldeck. Or you can use your own cement/sand product (see below).

As an Admixture to your own cement/sand product:

Add Liquid Acrylic Bonder/Admixture full strength (do not add water) to your own cement/sand product and mix well.

WARNING: CONTAINS ACRYLIC RESIN. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

KEEP OUT OF THE REACH OF CHILDREN

MADE IN THE U.S.A.

5 US GALLONS

E-Z PRODUCTS

888-439-7282

www.e-zpatch.com